



PROCAM-X30

SDI, HDMI, IP PTZ ZOOM 30X
CONFERENCE CAMERA

PROCAM-X30 is a multi video output PTZ conference camera for capturing high quality video in professional environments. Equiped with a Panasonic 1 / 2.7" CMOS 2.07 MPx sensor, combined with 2D and 3D noise reduction algorithm, this camera provides an high quality and clear image, even under low illumination conditions. It also features a x30 optical zoom, for perfect video capture of distant subjects in large areas..

The HDMI and 3G-SDI outputs return a full HD 1080p/60 video signal that is duplicated on an IP H.265/264 port for streaming, including RTMP for direct boradcasting on web platforms like YouTube or Facebook Live. Camera exists in dark grey color or white. Both elegant and robust, PROCAM-X30 is a professional multi-application PTZ camera, ideal for large conference rooms, congress centers, university amphitheatres, auditoriums, ...

Highlights

Panasonic 1 / 2.7" CMOS 2.07 MPx sensor	Full HD 1080p/60	HDMI, 3G-SDI and IP H.264/265 ouputs	30x optical zoom 16x digital zoom
65.1° FOV	Clear and clean image under low light conditions	Support RTMP streaming protocol	Reverse PTZ for ceiling installation
Support PoE power supply	Control by IP, RS-232, RS-485, IR	Exist in 2 colors: Dark grey or white	Application : large conference rooms, auditoriums, ...

HDMI, 3G-SDI
and IP outputs

Reverse PTZ
ceiling installation

White version

Panasonic CMOS
2.7Mpx sensor

30x optical zoom





PROCAM-X30

SDI, HDMI, IP PTZ ZOOM 30X
CONFERENCE CAMERA

Specifications

Sensor	1 / 2.7" CMOS Panasonic 2.07 Mpx
Lens	30x optical, f4.3mm – 129mm F1.8 – F2.8, x16 digital
Resolutions	1080p/60/50/30/25, 1080i/50/60, 720p60/50/30/25
Mini Illumination	0.5 Lux
Shutter speed	1/30s – 1/1000s
FOV	65.1° - 2.34° H / 58.9° - 2.11° V
PAN & Tilt range	340° horizontal, 120° vertical
Flip H & V	Support
Preset numbers	255

Inputs	1x Audio Line-In jack 3.5 mm f.
Oupputs	1x HDMI 1.3, 1x 3G-SDI 1x H.264/265 RJ-45
Communication	1x RS-232 I/O (8 pins), 1x IP (RJ-45), 1x RS-485 (2 terminal blocks)
Streaming protocols	TCP/IP, UDP, HTTP, RTSP, RTMP, DHCP, ONVIF
Power Supply	DC 12V or PoE
Power Consumption	12W
Dimensions	146 x 152 x 165 mm
Weight	1.35 Kg

Accessories included :

IR remote control, RS-232 adaptor, power supply

Accessories optional :

LCM-CB : Ceiling mount bracket
LCM-WB : Wall mount bracket
PCM-KEYBOARD : IP control keyboard

Model reference :

PROCAM-X30 : Dark grey color body
PROCAM-X30W : White body

